

# Preliminary Assessment Report Project 3024718, 4354 S HENDERSON ST

**Assessment Completed:** 6/16/2016

**Project Description:** Land Use Application to allow a 4-story building containing 30 apartment units and 2,000 sq. ft. of office space at ground level. Parking for 13 vehicles to be provided at grade. Existing structure to be demolished.

**Primary Applicant:** <u>Jeremy Rene</u>

This report lists the results of a preliminary assessment of your project requirements by various city departments. It's based on the project characteristics described on your site plan and preliminary application form. If your project required a pre-application site visit (PASV), the results of that site visit are also included. The goal of this report is to help you create a complete submittal package and reduce the need for corrections once your application has been submitted.

# **Next Steps**

- 1. Review the requirements in this report and contact the staff members listed below with questions.
- 2. If a street improvement plan is required, develop and submit it to the Seattle Department of Transportation (SDOT). The Seattle Department of Construction and Inspections (SDCI) will not accept your permit application until your street improvement plan is approved as 60% complete by SDOT. See SDOT Client Assistance Memo 2213 for guidance about the 60% complete approval process.
- 3. Schedule an appointment for permit application intake with SDCI. Please bring a copy of this report to your intake appointment.

#### **Questions About This Report**

If you have questions about the information in this report, contact the appropriate city staff member for each section.

#### **SDCI Drainage Requirements**

Eric Dripps, (206) 727-3676, Eric.Dripps@seattle.gov

#### **SDCI Land Use Requirements**

Maria Victoria G Cruz, (206) 615-1266, maria.cruz@Seattle.Gov

## **SDCI Preapplication Site Visit Requirements**

Yung Potts, (206) 727-8434, Yung.Potts@seattle.gov

# **Seattle City Light Requirements**

Benjamin Rushwald, (206) 733-9830

#### **Seattle Department of Transportation Requirements**

Joel Prather, (206) 615-0772, joel.prather@seattle.gov

### **Seattle Public Utilities Requirements**

Lan Chau, (206) 727-3584

#### **Water Availability**

SPU Staff, (206) 684-3333, SPUWaterAvailability@Seattle.Gov

#### **Other Resources**

- General questions about the permit process: Contact the SDCI Applicant Services Center (ASC) at 206-684-8850.
- User-friendly guides to city permitting processes: <u>SDCI</u> and <u>SDOT</u>.
- Detailed zoning information.
- Visit our <u>permit type pages</u> for step-by-step instructions and forms for preparing your application and plans for review.

# Requirements

# **SDCI Drainage Requirements**

The following requirements are based on the current stormwater and side sewer codes.

\*\*The new 2016 Stormwater Code becomes effective on January 1, 2016. Projects with an accepted application (successful SDCI permit intake) date after December 31, 2015 will be reviewed under the new code. The drainage requirements indicated below are based on the 2016 Stormwater Code. If your project will be submitted prior to January 1, 2016, please contact the SDCI Drainage Reviewer to determine drainage requirements.\*\*

# **Existing Public Drainage Infrastructure**

Storm drainage main location: **On property / S Henderson St** 

Storm drainage main size: 24-inch / 66-inch

Combined sewer main location: S Henderson St (King County Main)

Combined sewer main size: 48-inch

#### **Drainage**

A Build-over Agreement may be required with SPU for this project.

See <u>Tip 507, Build-Over and/or Re-Route Review and Approval Process</u>, for instructions on applying for a build-over review. Note: New easements or relinquishing existing easements requires City Council action prior to building permit approval, and may take up to 18 months. Revisions to existing easements are sometimes required for Construction Permits.

#### Infiltration Investigation Required: Yes

Projects that require On-site Stormwater Management, Flow Control, and/or Water Quality Treatment must first investigate infiltration feasibility before selecting other BMP's. See Seattle Stormwater Manual, Volume 3, Section 3.2 and Appendix D to determine infiltration feasibility. If feasible, infiltration testing per the requirements in Appendix D is required prior to application. Submit a completed Infiltration Checklist with the construction permit application. Checklists are available on the DPD Stormwater Code website. <a href="http://www.seattle.gov/dpd/codesrules/codes/stormwater/default.htm">http://www.seattle.gov/dpd/codesrules/codes/stormwater/default.htm</a>

Please note: projects that infiltrate 5,000 square feet or more of impervious surface area must conduct Groundwater Monitoring for a full wet season or one full year if infiltrating 10,000 square feet or more of impervious surface area. See Table 3.1 in Section 3.2.

#### **Project Type and Drainage Basin**

The storm drainage point of discharge (SMC 22.805.020) is located at: **Public storm drain system** 

Project Type: Parcel-based

Drainage Basin: Designated receiving water

# **Drainage Control Compliance**

Drainage Review Required: Yes

Drainage Control Review is required for this project per SMC 22.807.020. Submit a completed **Standard Construction Stormwater Control and Post Construction Soil Management (CSC/SOIL) Plan** and a

completed <u>Standard Drainage and Wastewater Control (DWC) Plan</u> including the **Site and Drainage Control Summary** from On-site Stormwater Management Calculator.

Note: For projects with 5,000 square feet or more of new plus replaced hard surface, a comprehensive drainage control plan, construction stormwater control plan, soil amendment plan, and drainage report shall be prepared by a licensed engineer.

#### Soil Amendment Required: Yes

All new, replaced, and disturbed topsoil shall be amended with organic matter per rules promulgated by the Director prior to completion of the project to improve onsite management of drainage water flow and water quality per SMC 22.805.030.A, 22.805.040.A, or 22.805.050.A. Complete the **Post Construction Soil Management Plan** on the Standard CSC/SOIL Plan.

On-site Stormwater Management Required: Yes

Parcel-based projects with 7,000 square feet or more of land disturbing activity, 1,500 square feet or more of new plus replaced hard surface or, if on a lot or parcel created or reduced in size on or after January 1, 2016, 750 square feet or more of new plus replaced hard surface, must implement **On-site Stormwater**Management (infiltration, dispersion, bioretention, green roofs, permeable pavement, rainwater harvesting, etc.) to manage runoff from all hard surfaces on-site per SMC 22.805.050.B. and Director's Rule 21-2015.

Submit an <u>On-site Stormwater Management Calculator</u> and show the On-site Stormwater Management BMP's and surface designation on the <u>Standard Drainage and Wastewater Control Plan</u>.

#### Flow Control Required: No\*

Based on the information provided, adherence to Flow Control Standards is not required for this project.

\*Note: if groundwater will be discharged to the public drainage system, Flow Control may be required. Projects which propose to permanently discharge groundwater shall comply with Minimum Requirements for Discharges to a Capacity-constrained System, SMC Section 22.805.050.A.6 and SMC Section 22.805.060.A.6.

#### **Water Quality**

No requirements

#### Wastewater

The wastewater point of discharge (SMC 21.16.070.B) is located at **Combined Sewer.** 

<u>King County Capacity Charge:</u> All homeowners and building owners in King County's service area (i.e. all Seattle Public Utility Combined and Sanitary Sewers) whose home or building was connected, reconnected or had a new service established to a sewage facility served by King County on or after Feb. 1, 1990 must pay a <u>King County Capacity Charge</u>. (King County Code No. 28.84.050.0.1)

# **Permanent and Temporary Dewatering**

Per SMC 21.16.110, the proposed project requires a separate side sewer permit for temporary dewatering based on the following: excavation greater than 12 feet deep.

The footing drain (if part of building plan) point of discharge (<u>DPD DR 4-2011</u>) is located at the following: <u>Public storm drain system.</u>

# **Side Sewer**

#### **Connections to Existing Side Sewers**

The existing side sewer for a new or converted building or dwelling unit may be reused pursuant to SMC 21.16.240. If there is an increase of dwelling units or buildings the <u>Side Sewer Evaluation and Certification Form</u> must be completed by a licensed engineer.

#### Fats, Oils, Grease (FOG)

For your information: In serving establishments (i.e restaurants, cafes, lunch counters, cafeterias, bars and clubs, hotels, hospitals, sanitariums, factory or school kitchens, or other establishments where grease is introduced into the drainage or sewage system), there may be additional requirements to control the discharge of fats, oils, and grease (FOG) into the sanitary sewer system.

Please contact: <u>Gary.Christiansen@seattle.gov</u> in SPU's FOG Program to determine pretreatment requirements to protect the municipal sewer system from FOG generated by food preparation and handling. Any internal plumbing modifications require a plumbing permit from King County Public Health 206-684-5198.

For more information, visit:

http://www.seattle.gov/util/MyServices/DrainageSewer/FatsOilsGrease/index.htm http://www.kingcounty.gov/healthservices/health/ehs/foodsafety/FoodBusiness.aspx

# **Other Requirements**

• For approval to connect or reuse the King County Main, contact Todd Keithahn at Todd.Keithahn@kingcounty.gov or 684-1369 If approval from King County to use their main is not received, a new connection to the storm main and a sanitary sewer main extension is required.

# **SDCI Land Use Code Requirements**

#### **Street Requirements**

Based on the scope of the proposed project, the following street improvements are required per Chapter 23.53 of the Seattle Municipal Code. Please review Right-of-Way Improvements Manual for design criteria (http://www.seattle.gov/transportation/rowimanual/manual/). Show required street improvements on your "enhanced site plan" at SDCI permit application intake. If an SDOT Street Improvement Plan (SIP) is required, please list SDOT project number and SDOT contact name on the enhanced site plan. Street Improvement Plans must be accepted by SDOT prior to SDCI permit application intake.

#### **S HENDERSON ST**

Street trees shall be provided in the planting strip according to Seattle Department of Transportation Tree Planting Standards. Contact SDOT Urban Forestry (for residential projects: (206) 684-TREE; for all others: (206) 684-5693), to determine species of tree and standards of planting. Please add a note to the site plan showing size, location and species of tree to be planted.

http://www.seattle.gov/transportation/treeplanting.htm.

Existing curbcuts that will no longer be used are required to be removed, and the curbline reinstalled, per SDOT standards.

# Alley Requirements Alley

Pave the width of the alley abutting the lot and the portion of alley between the lot and the connecting street. The Seattle Right of Way Improvements Manual (http://www.seattle.gov/transportation/stuse\_docs.htm) contains design details.

Improve the remainder of the alley so that it is passable to vehicles from street to street or provide a turnaround/cul-de-sac. The Seattle Right of Way Improvements Manual

 $(http://www.seattle.gov/transportation/stuse\_docs.htm)\ contains\ design\ details.$ 

A 2 foot dedication is required. Refer to SDOT CAM 2203. Please see http://www.seattle.gov/transportation/stuse\_docs.htm.

#### **Land Use**

Based on the project scope. SEPA may be required. See DPD Director's Rule 29-2015 for more details (http://web1.seattle.gov/dpd/dirrulesviewer/).

Design Review is required; see CAM 238 for more details. Departures from development standards should be identified as early as possible in the application process.

Alley access may be required

# **Other Requirements**

A presubmittal conference is required before to submitting an application. Details for preparing and submitting a presubmittal request form can be found at our Web site (http://www.seattle.gov/dpd/Publications/Forms/Building Permit/default.asp).

# **Pre-Application Site Visit (PASV) Requirements**

PASV report requirements may be subject to additions, changes, or modifications by the department. The purpose of the report is to alert the applicant that there may be unusual or complex site conditions that trigger requirements from the department regarding this project. **The applicant is responsible for providing all required documents at the intake appointment.** If you have questions about this report or the PASV process, please contact the SDCI Site Development Team at (206) 684-8860.

**Note:** Any project application associated with the development site can utilize the results from this PASV if the application is accepted by SDCI within 24 months of the above inspection date. After 24 months, the applicant must apply for another PASV. No extensions will be granted.

The site plan did not include the following existing or proposed elements:

No further notes.

## **ECA Mapping Unit and Type**

Non-ECA

#### **Earth Disturbance**

If excavation has the potential to encroach on adjacent property in order to facilitate construction activity, please provide documentation of consent from the adjacent property owner. Show area of proposed encroachment on the submitted drawings and detailed cross-sections.

If temporary cuts greater than 1h:1v will be required in order to facilitate construction activity, please provide a geotechnical engineer's verification that soil conditions allow cuts to stand unsupported. Include detailed cross sections.

Please show all existing and proposed retaining walls/rockeries and the exposed height.

If shoring will be required, please provide submittals by geotechnical and structural engineers and show the proposed system on the submitted drawings. Include detailed cross sections.

# Existing ROW Conditions S HENDERSON ST

Street conditions:

Asphalt paving

Visible pavement width is: 54

Curb conditions:

Curb adjacent to site

Concrete

Approximate curb height: 5.5 " inches

A storm inlet is located <350 ft from the site and prior to crossing a public right of way. Water will cross ADA ramp at curb for Chief Seth Trail

It appears that drainage from that discharge point will remain in the gutter line all the way to the nearest inlet structure, but this assessment is preliminary and it is the responsibility of the applicant to meet all relevant SW code requirements.

#### Alley

Unimproved

Comments: Over grown with vegetation and is fenced off by surrounding neighbors.

#### **Potential Impacts to Seattle Parks Property**

No parks property in vicinity

#### **Tree Protection**

Trees greater than 6 inches in diameter as measured 4.5 ft above ground are present on the site but not shown on the site plan. Show the dripline of

- 1) all trees on the site,
- 2) adjacent trees that encroach on the site that are greater than 6 inches in diameter as measured 4.5 ft above ground, and
- 3) all trees located in the adjacent ROW.

Include common and scientific names for all trees shown. For more information, see <u>Director's Rule 16-2008</u> and <u>Tip 242</u>.

2 tree in ROW

#### **Construction Stormwater Control**

All projects with earth disturbance, regardless of size, require temporary and permanent stormwater control in accordance with the Construction Stormwater Control (CSC) Technical Requirements Manual (<u>DR 21-2015</u>, Volume 2).

# **Show the following on the Construction Stormwater Control and Soil Amendment Standard Plan:**

Place filter fabric, straw bales, straw wattles, or other approved equal to control construction stormwater runoff. Required along the following property lines:

Place compost socks, compost berms, filter fabric fencing, straw bales, straw wattles, or other approved perimeter control BMPs to eliminate construction stormwater runoff.

Show the location of a stabilized construction access to the site; show methods to eliminate uncontrolled conveyance of mud and dirt into the right of way (ROW).

Cover bare soil with compost blankets, straw, mulch, matting, or other approved equal to control construction stormwater runoff.

Cover stockpiles and bare slopes with compost blankets, tarps, matting or other approved equal to control construction stormwater runoff.

A First Ground Disturbance inspection is required before any ground disturbance related to this permit, including demolition, tree cutting, clearing, grubbing, and grading. After your permit is issued, schedule an inspection by calling (206) 684-8900 or online at <a href="http://web1.seattle.gov/DPD/InspectionRequest/default.aspx">http://web1.seattle.gov/DPD/InspectionRequest/default.aspx</a>.

# **Inspectors Notes**

No further notes.

# **Seattle City Light Requirements**

#### **Notes to Applicant**

For new service, please contact the Electrical Service Representative for your area several months before new service is required to determine your electric service design, service location and what kind of service is available at the building site. An Application for Electrical Service must be submitted to Seattle City Light. The Electrical Service Representative should also be contacted to coordinate electrical disconnections prior to demolition and temporary power for construction. Your Electrical Service Representative is: Percy Schlimm, 206-386-1735, percy.schlimm@seattle.gov. Be advised that it is the applicant's responsibility to seek guidance from City Light. Failure to contact City Light early in the permit process could severely impact your project's scope, schedule and budget. This responsibility rests solely with the applicant.

## **SDOT Requirements**

The City of Seattle's Right-of-Way Improvements Manual (ROWIM) and SDOT's Street & Sidewalk Pavement Opening and Restoration (PORR) Director's Rule 2004-02 may be accessed from SDOT's Street Use website at: http://www.seattle.gov/transportation/stuse\_docs.htm. Whenever possible, specific reference notation for these two design documents is noted next to the design characteristics below. Be advised that these specific section and chapter references are provided as preliminary guidance only and are not comprehensive in scope.

#### **SDOT Permitting Information**

Initial Review Deposit: \$2,500

SDOT Plan Requirements: Engineered plan

SDOT Permit Requirements: Group 3: Street Use Major (Type 45). A 60% complete street improvement plan (SIP) must be approved by SDOT prior to your DPD construction intake appointment. SIP Design Guidance is required for 60% complete SIP approval; apply early. Please visit SDOT's Street Use website at: <a href="http://www.seattle.gov/transportation/stuse\_sip.htm">http://www.seattle.gov/transportation/stuse\_sip.htm</a> to obtain SDOT Client Assistance Memos (CAMs) and application materials to assist in developing your street improvement plan (SIP).

All private encroachments in the public right-of-way (ROW) require a 30-day permit that is renewed annually.

# **Street Improvement Requirements S HENDERSON ST**

SDOT Urban Forestry requires protection and retention of existing trees in the right-of-way unless specifically exempted. Refer to the Right-of-Way Improvements Manual (ROWIM) 4.14.

Coordinate with SDOT UF for evaluation/recommendations on existing ROW trees.

Street trees are required. SDOT Urban Forestry recommends providing street trees in a 5'-wide (minimum) planting strip, located between the sidewalk and the curb. If existing conditions preclude the preferred location, street trees can be accommodated adjacent to the right-of-way on private property. Per SMC 15.43.040, private property owners are responsible for the planting and maintenance of street trees in accordance with Standard Plan 100 and SDOT's Street Tree Manual. Refer to the Right-of-Way Improvements Manual (ROWIM) 4.14 for design criteria. Coordinate with SDOT UF.

All improvements on private property must accommodate the right of way elevation at the property line using the standard cross-section in the ROWIM. Right of way grading may be required to provide vehicular and pedestrian access that meets the standard cross-section.

New/replacement sidewalk: See Seattle Right of Way Improvements Manual (ROWIM) as well as the City of Seattle Standard Plan 420, 421 and 422. Repair & restoration of existing as needed.

New/Replacement Curb: See Seattle Right of Way Improvements Manual (ROWIM) and the City of Seattle Standard Plan 410. Construct new curb & restoration @ existing drwy closure.

# Alley Requirements Alley

Alley Grading: Standard alley cross section at established grade for portion of alley being improved. See Seattle Right of Way Improvements Manual (ROWIM) chapter 4. Apply for SDOT SIP Design Guidance. See SDOT CAM 2211.

New/replacement turnaround/cul-de-sac. See Seattle Right of Way Improvements Manual (ROWIM) section 4.22. If your project is proposing to install a new turnaround/cul-de-sac or is proposing to change the alignment of an existing turnaround/cul-de-sac apply for SDOT SIP Design Guidance. See SDOT CAM 2211.

Alley Drainage: Required for portion of alley being improved. A drainage review is required for any project which involves more than 750 sq ft of land disturbing activity in the public right-of-way. See Seattle Right of Way Improvements Manual (ROWIM) section 4.17.

Access via unopened/unimproved/unpaved alley. Grading, drainage and paving may be required. See Seattle Right of Way Improvements Manual (ROWIM) for improvement requirements.

# **Discretionary ROW Improvements**

Utilities such as poles, utility vaults, and fire hydrants may need to be relocated to accommodate your required street improvements. See Right of Way Improvement Manual (ROWIM) section 4.20 for clearance requirements.

Other recommendations: Potential public sanitary sewer main extension per SDCI if connection to KC main is not allowed.

# **SPU Requirements**

#### **Flow Control Compliance**

Soil Amendment. Retain and protect undisturbed soil in areas not being developed, and prior to completion of the project, amend all new, replaced, and disturbed topsoil (including construction lay-down areas) with organic matter to the extent required by and in compliance with the rules promulgated by the Director.

All roadway projects with 2,000 square feet or more of new plus replaced hard surface or 7,000 square feet or more of land disturbing activity shall meet the Minimum Requirements for On-site Stormwater Management contained in Section 22.805.070, to the extent allowed by law, except as provided in subsection 22.805.060.E.

In addition to applicable minimum requirements for flow control in subsection 22.805.060.C.1 through subsection 22.805.060.C.5, roadway projects discharging into a capacity-constrained system or its basin shall also comply with subsection 22.805.080.B.4 (Peak Control Standard) if the total new plus replaced hard surface is 10,000 square feet or more.

#### **Stormwater Treatment**

No water quality treatment is required

## **Water Availability**

Your water availability assessment has been approved.

Water Availability Certificate reference number: 20160642 Water Availability Certificate status: Approved with No Changes

Prepared by: Michael Barrett

#### **Existing Water System Information**

Proximity of nearest fire hydrant is: 132 feet E of property. Meets standards.

Water Main:

Size: 8 inches Material: Cast Iron Class: C

StandardAbutting

Water Main is available to serve in: S Henderson Street

Distance of main to N margin of street is 27 feet.

Public ROW width is 80 feet.

Water Service(s):

Size: 3/4" Material: Copper

#### **Solid Waste**

Your project is fronted by a major arterial. An alternate location for pickup of your solid waste is required. For questions about solid waste requirements, contact Liz Kain, (206) 684-4166, <u>Liz.Kain@seattle.gov</u> and see CAM 1301; Solid Waste: Information for Developers.

Your project is fronted by a bike/bus/transit-only lane. An alternate location for pickup of your solid waste is required. For questions about solid waste requirements, contact Liz Kain, (206) 684-4166, <u>Liz.Kain@seattle.gov</u> and see CAM 1301; <u>Solid Waste: Information for Developers</u>.

For all multifamily, commercial, and industrial properties, the requirements for solid waste storage and pickup are outlined in SPU CAM 1301, available on the web at:

http://www.seattle.gov/util/stellent/groups/public/@spu/@csb/documents/webcontent/cos 004542.pdf. For questions about solid waste requirements, contact Liz Kain, (206) 684-4166, Liz.Kain@seatte.gov.

# **Other Requirements**

Owners of residential property occupied by a tenant who will be displaced by housing demolition, substantial rehabilitation, change of use, or removal of use restrictions may need to obtain a Tenant Relocation License. Refer to SDCI Tip 123, Seattle's Tenant Relocation Assistance Ordinance, for further information and instructions or call (206) 684-7979.

If your project involves additions or modification to or demolition of an existing building that contains four or more dwelling units or 4,000 square feet or more of non-residential area, and the building is a designated historic landmark or is 50 years old and meets the criteria set forth in SMC 25.12 for landmark designation, SEPA is required. Please contact the Department of Neighborhoods at (206) 684-0228 or www.seattle.gov/neighborhoods/preservation to determine if your building is a designated landmark of if a referral is necessary to determine if the building meets the criteria in SMC 25.12. Refer to Tip 208 for information regarding the application requirements for a SEPA review and Tip 3000 for information regarding landmarks and historic preservation.

If the scope of your proposed project changes before your SDCI intake appointment or SDOT street improvement plan application, the requirements in this report may change. If there are municipal code and ordinance changes before our SDCI intake appointment, the project must meet the new code requirements. Additional street improvement requirements may be triggered if a permit application for a development project on adjacent property is also undergoing review.

Please be aware that all persons or companies working within the City limits, including all contractors, subcontractors, permit expeditors and other service providers are required to possess a valid City of Seattle business license. This license is required in addition to any other licenses required by the State of Washington, such as a contractors' license or state business license. For more information about City of Seattle business licenses, please contact inspector Michale Crooks at 206-684-8871, <a href="Michale.Crooks@seattle.gov">Michale.Crooks@seattle.gov</a>, or visit the <a href="Licensing and Tax Administration Division website.">Licensing and Tax Administration Division website.</a>